













X-Loupe [®] ForteLite-TG Specification	
Control Unit	
Function	Power On, Off / Light Channel Switch / Dimming Control
External Battery (not included)	Recommend: SONY V-mount BP series rechargeable battery *For shipping safety, product package come without battery
Power Supply	(1) External Battery (see the user manual of battery) (2) Power adapter* (INPUT: 100-240V~1.5A, 50-60Hz / OUTPUT: DC 19V, 4.7A) included in the product set. Charging via a wall outlet. *This adapter does not support V-mount battery charging; only use the dedicated charger for SONY V-mount battery charging.
Material	Steel, Aluminum, ABS
Operation Environment	0 ~ 40°C
Weight	1160g (Max)
Dimension (mm)	215(L) x 120(W) x 55(H)
Use in conjunction with Control Unit	Pier-mount downlight
Compatible with camera	OM System (former OLYMPUS) Tough TG
Mounting Method	Magnet mount
Filter	49mm (outside diameter \leq 54mm, thickness \leq 5mm) / Glass
Channel & Light source	Multi-channel. (2 bands standard, others optional, up to 4 channels available) Light Pack1: Latent Fingerprint Light Source - IR / White light (for Anti-Stokes powders / Regular)
LED Number	Each channel x 48
Power Consumption	55W (Max)
Dimming intensity	Intensity is dimmable from 1% to 100% (default setting 50%)
Dimension (mm)	145(L) x 115(W) x 128(H)
Weight	735g (Max)
Material	Aluminum, ABS, RoHS compliant
Power cable length	30cm
Operation Environment	0 ~ 40°C

^{*}We (Lumos Tech.) reserves the right to change the product appearance or specification. The contents of catalogs / manuals are subject to change without prior notice.









7th floor, No.8, Wanhe St., Wenshan District, 11653 Taipei City, Taiwan, R.O.C. TEL:886-2-2230-1168 FAX:886-2-2239-2112 e-mail:contact@lumos.com.tw www.x-loupe.com



^{*}The system only support and to be used with OLYMPUS Tough TG for the best effect.